



HCM-480

| | | | | | |
|----------------------------|--|---|--|--|--|
| DESCRIPTION: SEAL | | UNLESS OTHERWISE SPECIFIED | | CINCINNATI TEST SYSTEMS, INC. 5555 DRY FORK RD. CLEVELAND, OH 45002 | |
| MATERIAL: 90 DURO URETHANE | | 1) BREAK ALL SHARP CORNERS | | CUSTOMER | |
| FINISH: | | 2) TOLERANCES: 1 PLACE DECIMAL $\pm .06$ [0.3mm] 2 PLACE DECIMAL $\pm .02$ [0.03mm] 3 PLACE DECIMAL $\pm .005$ [0.015mm] ANGULAR DIMS $\pm 0^\circ 30'$ | | TITLE | |
| QUANTITY: 2 | | 3) ∇ INDICATES 500 MAXIMUM FINISH REQ'D ON SURFACES WITHOUT A SYMBOL | | LEAK TEST MACHINE | |
| HEAT TREAT: | | 4) DRILLED AND COUNTERBORED HOLE DIAMETERS: -.005 / +.015 [-0.13mm / +0.4mm] | | DATE | |
| | | SolidWorks 2005 | | DWG NO. J20047-D-010 | |
| | | | | SCALE: 12:1 | |
| | | | | SHEET | |

